LAWN / CROSS-COUNTRY

STREETS / PAVED AREAS

TOPSOIL & SOD OR SEED

4"

1'

APPROVED GRANULAR NON-ORGANIC BACKFILL MATERIAL PLACED AND COMPACTED IN ONE FOOT (1') (MAX.) LIFTS.

WARNING TAPE PER CONN. GENERAL STATUTE SECTION 16-345, AS AMENDED, PLACED 12" (MIN.) TO 24" (MAX.) ABOVE TOP OF PIPE.

SAND BLANKET

12" MIN.

PIPE, AS SPECIFIED

1/2 O.D. PIPE

FILTER FABRIC

1/2 O.D. PIPE

3/4" BROKEN TRAPROCK

6" MIN.

FILTER FABRIC (SEE NOTE) OVERLAP MIN. 6" BOTH WAYS

O.D. PIPE

1'   1'

__SECTION__

12" SAND MIN.

STONE

6" MIN.

NOTES:

1. SEE STANDARD DETAIL FOR CLAY STOPS WHERE NECESSRAY, PG. VI-54

2. FILTER FABRIC SHALL BE NONWOVEN AND SHALL MEET AASHTO M288-00, CLASS 2

1'   2'-6"   1'

PIPE - IN GROUND WATER

NOT TO SCALE

TOWN OF SOUTH WINDSOR STANDARD DETAIL	TYPICAL SANITARY SEWER TRENCH SECTION	APPROVED
MARCH, 2005	REVISED:	PUBLIC WORKS DIRECTOR

SD-50

SEWTRENCH.DWG